



FE-134AD



FE-133AD



FE-132AD



FE-131AD

Las incubadoras Felisa® con control digital microcontrolado, sistema "Auto-tuning", hasta 16 perfiles de temperatura y control de rampas. Comunicación digital USB mediante software de adquisición de datos y graficado.

Gravity convection or mechanical convection with analog temperature control or microcontrolled digital control. Interior made of stainless steel and exterior made of steel finished in anti-corrosive enamel.

### Features

- Microcontrolled digital control with LCD screen, to observe programmed operating temperatures, cycle time and process status.
- Easy programming in the temperature control now incorporated with "Autotuning" system.

- System with security alarms with high and low temperature limits.
- Fault detection system.
- Timer up to 75 hours.
- Up to 16 temperature profiles and ramp control.
- USB digital communication, through graphic and data acquisition software.
- Models with analog temperature control (thermometer required).
- Heating element designed to provide optimal uniformity.
- With air flow regulation.
- Each equipment has two shelves.

Modelo Model	Capacidad Capacity	Tiempo temp. Máx. Max. temp. time	Estabilidad Stability	Voltios Volts	Watts Watts	Amperes Amps	Interior WxDxH* Interior WxDxH*	Exterior WxDxH* Exterior WxDxH*	Peso Weight
FE-131	38.0 L	40 min	± 0.5° C	120	120	1.0	33.0 x 35.0 x 33.0 cm	50.0 x 51.0 x 70.0 cm	32.0 Kg
FE-131A	38.0 L	40 min	± 0.3° C	120	180	1.5	33.0 x 35.0 x 33.0 cm	50.0 x 51.0 x 70.0 cm	33.0 Kg
FE-131D	38.0 L	40 min	± 0.5° C	120	120	1.0	33.0 x 35.0 x 33.0 cm	50.0 x 51.0 x 70.0 cm	32.0 Kg
FE-131AD	38.0 L	40 min	± 0.3° C	120	180	1.5	33.0 x 35.0 x 33.0 cm	50.0 x 51.0 x 70.0 cm	33.0 Kg
FE-132	83.0 L	50 min	± 0.5° C	120	240	2.0	44.0 x 40.0 x 47.0 cm	62.0 x 56.0 x 84.0 cm	44.0 Kg
FE-132A	83.0 L	50 min	± 0.3° C	120	300	2.5	44.0 x 40.0 x 47.0 cm	62.0 x 56.0 x 84.0 cm	46.0 Kg
FE-132D	83.0 L	50 min	± 0.5° C	120	240	2.0	44.0 x 40.0 x 47.0 cm	62.0 x 56.0 x 84.0 cm	44.0 Kg
FE-132AD	83.0 L	50 min	± 0.3° C	120	300	2.5	44.0 x 40.0 x 47.0 cm	62.0 x 56.0 x 84.0 cm	46.0 Kg
FE-133	141.0 L	60 min	± 0.5° C	120	400	3.3	60.0 x 50.0 x 47.0 cm	77.0 x 66.0 x 84.0 cm	56.0 Kg
FE-133A	141.0 L	60 min	± 0.3° C	120	460	3.8	60.0 x 50.0 x 47.0 cm	77.0 x 66.0 x 84.0 cm	58.0 Kg
FE-133D	141.0 L	60 min	± 0.5° C	120	400	3.3	60.0 x 50.0 x 47.0 cm	77.0 x 66.0 x 84.0 cm	56.0 Kg
FE-133AD	141.0 L	60 min	± 0.3° C	120	460	3.8	60.0 x 50.0 x 47.0 cm	77.0 x 66.0 x 84.0 cm	58.0 Kg
FE-134A	373.0 L	70 min	± 0.5° C	120	480	4.0	97.0 x 70.0 x 55.0 cm	117.0 x 94.0 x 100.0 cm	123.0 Kg
FE-134AD	373.0 L	70 min	± 0.5° C	120	540	4.5	97.0 x 70.0 x 55.0 cm	117.0 x 94.0 x 100.0 cm	127.0 Kg
FE-135A	300.0 L	70 min	± 0.5° C	120	920	7.6	60.0 x 50.0 x 100.0 cm	77.0 x 63.0 x 163.0 cm	115.0 Kg
FE-135AD	300.0 L	70 min	± 0.5° C	120	920	7.6	60.0 x 50.0 x 100.0 cm	77.0 x 63.0 x 163.0 cm	115.0 Kg

A: Convección mecánica / Mechanical convection

D: Control digital / Digital control

\*WxDxH: Ancho x profundidad x alto / Width x depth x height.

Temperatura ambiente: + 5° a 100° C / Ambient temperature: + 5 to 100° C

Cámara: Acero inoxidable / Chamber: Stainless steel